## Stainless Steel End Style Straight Connector



## **Product Overview : Stainless Steel End Style Straight Connector**

• **Material**: Location A, C, F are made of 304 stainless steel, B. E are made of chemigums, and D is made of stainless steel

• Thread : PG, G

• Color : Metalic (White)

• Working Temperatures : -40°C to 100°C, Instantaneously can be 120°C

• Protection Degree : IP65

- **Property**: made of 304 stainless steel, nice looking, compact structure, strength higher than normal conduit connector. Ferrule design make conduit connection tightly, easy assembly, and strong pull resistance.
- Water resistant, dust resistant, inactive with salts, acid and alkali resistance, alcohols, oils and greases as well as general solvent.
- G style thread standard, others should be customized.



## PG Type

Product Model	G	Metric	Thread Standard (PG)	Thread O.D (D1) mm	Thread Length (L1) mm.	SW (mm.)	Package Unit (Unit/Pack)
DPB-6-PG7	3/16"	Ф 6	PG7	12.5	7	18/16	100
DPB-8-PG9	5/16"	Ф 8	PG9	15.2	8	24/22	50
DPB-10-PG9	1/4"	Ф 10	PG9	15.2	8	24/22	50
DPB-13-PG11/PG13.5	3/8"	Ф13	PG11/PG13.5	18.6/20.4	10	26	50
DPB-16-PG13.5/PG16	1/2"	Ф 16	PG13.5/PG16	20.4/22.5	10	30	50
DPB-20-PG21	3/4"	Ф20	PG21	28.3	12	35	25
DPB-25-PG29	1"	Ф 25	PG29	37	12	43	20
DPB-32-PG29	1 1/4"	Ф32	PG29	37	14	52	10
DPB-48-PG36/PG42	1 1/2"	Ф38	PG36/PG42	47/54	14	60	10
DPB-51-PG48	2"	Ф51	PG48	59.3	15	75	5

## G Type

Product Model	G	Metric	Thread Standard (G)	Thread O.D (D1) mm	Thread Length (L1) mm.	SW (mm.)	Package Unit (Unit/Pack)
DPB-6-G1/4	3/16"	Ф 6	G1/4"	13.2	7	18/16	100
DPB-8-G3/8	5/16"	Ф 8	G3/8"	16.5	8	24/22	50
DPB-10-G3/8	1/4"	Ф 10	G3/8"	16.5	8	24/22	50
DPB-13-G3/8	3/8"	Ф13	G3/8"	16.5	10	26	50
DPB-16-G1/2	1/2"	Ф16	G1/2"	21.3	10	30	50
DPB-20-G3/4	3/4"	Ф20	G3/4"	26.6	12	35	25
DPB-25-G1	1"	Ф25	G1"	33.4	12	43	20
DPB-32-G1-1/4	1-1/4"	Ф32	G1-1/4"	42.1	14	52	10
DPB-48-G1-1/2	1-1/2"	Ф38	G1-1/2"	47.8	14	60	10
DPB-51-G2	2"	Ф51	G2"	59.6	15	75	5
DPB-64-G2-1/2	2-1/2"	Ф 64	G2-1/2"	75.1	20	89/87	2

