

## SILICONE HOSE, 2 PLY, UNI M8L / M9 SILVER / M2 VITON

### [ Product Overview ]

- Detail :**
- 2 Ply-Silicone (M9) / Viton (M2 Viton) coated glass fibre fabric.
  - Embedded broze plate steel wire helix.
  - Twin outer glass cord.
  - Light, Link resistant.
  - Low air friction loss properties due to additional inner layer.
  - always smooth bore also in tight bends.
  - Good application in low pressure range.



**Temperature :** -80°C ~ 310°C


**Options :** Other colour (silver and black)

Dia. Inside (mm.)	Dia. Outside (mm.)	Weight (KG/M)	Bendradius (mm.)	Pressure (BaR)	Vacuum mm WS/mm WG	Length (m.)	Dia. Inside (mm.)	Dia. Outside (mm.)	Weight (KG/M)	Bendradius (mm.)	Pressure (BaR)	Vacuum mm WS/mm WG	Length (m.)
32	35.20	400	60	2.5	5800	4	127	131.70	1600	280	1.5	2100	4
38	41.20	420	70	2.4	5800	4	140	144.70	1700	280	1.4	1800	4
41	44.20	500	80	2.4	5800	4	152	157.20	1800	300	1.1	1700	4
51	54.74	530	100	2.4	5300	4	160	165.20	1900	310	0.9	1500	4
57	60.74	570	110	2.3	5300	4	178	183.20	2050	400	0.8	1400	4
63	66.74	600	120	2.2	4600	4	203	208.20	2250	400	0.6	1000	4
70	73.74	800	140	2.2	4600	4	229	234.20	2500	470	0.5	800	4
76	79.74	900	150	2.1	4400	4	254	259.20	2700	500	0.4	700	4
102	106.20	1270	200	1.8	3500	4	305	310.20	3250	700	0.2	500	4

## UNI M9S 1.25 MM FDA LINER

### [ Product Overview ]

- Detail :**
- Line inside 1.25 mm. silicone 65 shore A VMQ food FDA/BGA
  - 0.3 mm. silicone polyester Fabric
  - Copper coated strong spring wire
  - Steel silicone coated glass
  - Red Oxide
  - Twin glass cord silicone coated



**Temperature :** -60°C ~ 220°C Optional version to 300°C

Dia. Inside (mm.)	Dia. Outside (mm.)	Weight (KG/M)	Bendradius (mm.)	Pressure (BaR)	Vacuum mm WS/mm WG	Length (m.)	Dia. Inside (mm.)	Dia. Outside (mm.)	Weight (KG/M)	Bendradius (mm.)	Pressure (BaR)	Vacuum mm WS/mm WG	Length (m.)
32	35.20	400	60	2.5	5800	4	127	131.70	1600	280	1.5	2100	4
38	41.20	420	70	2.4	5800	4	140	144.70	1700	280	1.4	1800	4
41	44.20	500	80	2.4	5800	4	152	157.20	1800	300	1.1	1700	4
51	54.74	530	100	2.4	5300	4	160	165.20	1900	310	0.9	1500	4
57	60.74	570	110	2.3	5300	4	178	183.20	2050	400	0.8	1400	4
63	66.74	600	120	2.2	4600	4	203	208.20	2250	400	0.6	1000	4
70	73.74	800	140	2.2	4600	4	229	234.20	2500	470	0.5	800	4
76	79.74	900	150	2.1	4400	4	254	259.20	2700	500	0.4	700	4
102	106.20	1270	200	1.8	3500	4	305	310.20	3250	700	0.2	500	4