



Polyurethane Flexible Duct Hose (Anti Static)

Polyurethane Flexible Duct Hose [Anti Static]

[Product Overview]

Application	Excellent for conveyance applications requiring abrasion-resistance, Flexibility and compressibility, Widely used in wood-wording, Electronic, Air conveyance, fume extraction, gas, oil chemical liquids and other ventilation application.
Structure	Anti static by grounding the copper wire, with rigid, PVC helix.
Working Temp.	-40°C to 125°C
Color	Clear-white
Wall & Spiral	Top grade of polyurethane with pvc and copper wire.



Part No	Inch.	I.D. (mm.)	O.D. (mm.)	Length (m./Roll)	WP.PSI (Psi.)	Bending Radius (mm.)
DB 025	1"	25	32	20	2.2	50
DB 032	1 1/4"	32	37	20	2.0	80
DB 038	1 1/2"	38	45	20	2.0	100
DB 050	2"	51	59	20	2.0	128
DB 065	2 1/2"	63	72	20	1.8	158
DB 075	3"	76	87	20	1.8	188
DB 100	4"	102	112	20	1.5	300
DB 125	5"	127	138	20	1.3	400
DB 150	6"	152	164	20	1.0	500
DB 175	7"	178	190	20	0.8	600
DB 200	8"	203	215	20	0.5	700