



## Product Overview

Metal



- Material : Brass with nickel plated
- Ambient Temperature : -40°C to 100°C, Temporary to 120°C
- Protection Degree : IP54
- Application : To close unused cable gland entries and normal integrity of the equipment
- Accessories : Locknut, Sealing washer.
- Remark :
  - If you need \*Hexagonal Series\* Please Specify \*H\* at the end
  - \*\* TPE-SC-M20-H\*\*



Can add more Thread Length (GL) - **Optional\***

### PG TYPE

Product Model	Thread	AG (mm.)	H (mm.)	GL (mm.)	Spanner Size	Qty / Bag
TPE-SC-PG7	PG7	12.5	8.0	5.0	14.0	100
TPE-SC-PG9	PG9	15.2	9.0	6.0	18.0	100
TPE-SC-PG11	PG11	18.6	9.0	6.0	20.0	100
TPE-SC-PG13.5	PG13.5	20.4	9.5	6.5	22.0	100
TPE-SC-PG16	PG16	22.5	9.5	6.5	24.0	100
TPE-SC-PG21	PG21	28.3	11.0	7.5	30.0	50
TPE-SC-PG29	PG29	37.0	12.0	8.0	40.0	20
TPE-SC-PG36	PG36	47.0	15.0	9.0	50.0	10
TPE-SC-PG42	PG42	54.0	16.0	10.0	57.0	10
TPE-SC-PG48	PG48	59.3	16.0	10.0	64.0	10

### M TYPE

Product Model	Thread	AG (mm.)	H (mm.)	GL (mm.)	Spanner Size	Qty / Bag
TPE-SC-M8	M8x1.0	8.0	8.0	5.0	12.0	100
TPE-SC-M10	M10x1.0	10.0	8.0	5.0	12.0	100
TPE-SC-M12	M12x1.5	12.0	8.0	5.0	14.0	100
TPE-SC-M16	M16x1.5	16.0	9.0	6.0	18.0	100
TPE-SC-M18	M18x1.5	18.0	9.0	6.0	20.0	100
TPE-SC-M20	M20x1.5	20.0	9.5	6.5	22.0	100
TPE-SC-M22	M22x1.5	22.0	9.5	6.5	24.0	100
TPE-SC-M24	M24x1.5	24.0	10.0	6.5	27.0	100
TPE-SC-M25	M25x1.5	25.0	10.0	6.5	27.0	100
TPE-SC-M30	M30x1.5	30.0	10.0	6.5	32.0	50
TPE-SC-M32	M32x1.5	32.0	11.0	7.0	36.0	50
TPE-SC-M36	M36x1.5	36.0	12.0	8.0	40.0	20
TPE-SC-M40	M40x1.5	40.0	13.0	8.0	45.0	20
TPE-SC-M50	M50x1.5	50.0	15.0	9.0	55.0	10
TPE-SC-M60	M60x1.5	60.0	16.0	10.0	64.0	10
TPE-SC-M63	M63x1.5	63.0	16.0	10.0	68.0	10
TPE-SC-M72	M72x2.0	72.0	16.0	10.0	78.0	10